



Page 2 of 2

I have enclosed for your reference the S0811 Microtunnelling and Pipe Jacking (Supplemental) Specification which accompanied the aforementioned Tender Circular and is to be used in conjunction with Qatar Construction Specification 2010 (QCS 2010) on the IDRIS Programme – Package 1 – Lateral Interceptor Sewers – Contracts LIS-01, LIS-02 & LIS-03.

I would further point out that pipe jacking distances are likely to be in the range of 300 – 500m owing to the specified requirement for maximum spacing between access manholes.

I note your comments in your letter regarding the durability advantages of Polymer Concrete Pipes, your laboratory testing capability and your local production capability. You may wish to consider contacting the tendering Contractors for Contracts LIS-01, LIS-02 & LIS-03, who may wish to offer Polymer Concrete Pipes as part of their forthcoming Tender submissions.

I hope this response adequately addresses your enquiry. Thank you for your interest in the IDRIS Programme.

Regards,

Muhannad I. H. Hammad  
Acting Manager of Drainage Networks Projects  
Department

Cc: Jassim Salman A Al Sayegh; Nasser Yousef A Fakhroo; Infrastructure Affairs; President Office

ص.ب: ٢٢١٨٨، الدوحة - قطر، تليفون: +٩٧٤ ٤٤٩٥٠٠٠٠، فاكس: +٩٧٤ ٤٤٩٥٠٩٠٠٠

P.O. Box : 22188, Doha - Qatar, Tel. : +974 44950000, Fax : +974 44950900

[www.ashghal.gov.qa](http://www.ashghal.gov.qa)